



**JOB NAME:**

**CAT#:**

**TYPE:**

## APPLICATIONS

This MFL series is a stylish contemporary bath fixture with choice of brushed nickel "BN" or bronze ends "BZ". Mix and match with complementary close to ceiling, surface or wall sconce. For use in indoor applications where aesthetics and quality are important, such as residential bathrooms or nursing homes.

- Die-formed Cold-rolled Steel
- Linear sided prismatic lens of extruded acrylic
- UL, cUL Listed for damp locations, Energy Star Listed

The most economical, practical, and user friendly series of LED fixtures with energy savings, quality of light, long life and hassle-free maintenance/ EZLED fixtures are UL listed with the latest LED T8 bypass lamps. These fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required). They also provide the flexibility to change the wattage and color temperature at any time. Are you concerned about maintenance with an LED array and driver fixture? EZLED resolves that issue by utilizing a self-contained LED lamp that fits into your fixture just like the classic fluorescent tube. The fixture performance will evolve over time with the evolution of the T8 LED lamp technology, and our five-year warranty guarantees a reliable, high quality product.



## FEATURES & BENEFITS

Our EZLED fixtures come standard with SaveGreen T8 LED lamps. They are available in different wattage, lumens, and color temperature options (see lamp options and specifications at [www.savegreenlighting.com](http://www.savegreenlighting.com)).

- $L_{70} > 50,000$  hrs.
- Operating temperature: -20°C to 50°C
- Color Temperature: 3500K, 4000K, 5000K
- G13 pins (same as fluorescent linear T8 bipin)
- AC100-277V
- Integral driver (non-isolated) eliminates the need for external driver or ballast
- Environmentally friendly, no mercury used
- UL Classified
- Min CRI 80
- 5 year warranty

### Optional Dimming

The 4 foot lamps are available with a dimming option. Specially designed dimming lamps require an external driver that runs 1 or 2 lamps (more than 2 lamps require multiple external drivers).

### Emergency Options

The standard EZLED lamps require an inverter or an all-in-one emergency kit that includes LED array, battery, and driver. Dimmable T8 LED with external driver works with standard LED EM in it.

## DIMENSIONS

2 fixture - 24.75"L x 6.0"W x 4.25"H  
4 fixture - 48.60"L x 6.0"W x 4.25"H

**Note: In order for UL safety certification to be valid, only approved lamps may be installed in the fixture and must be shipped with the fixture from the factory.**





JOB NAME:

CAT#:

TYPE:

**ORDERING**

EXAMPLE: MFL 1 17 L7W LED SN 30 INV5

**MFL**

1. SERIES	2. # OF LAMPS	3. LAMP TYPE	4. LAMP WATTAGE	5. CONFIGURATION	6. TRIM COLOR	7. COLOR TEMP
<b>MFL</b>	<b>1</b> 1 Lamp	<b>17</b> 17 inch T8	<b>T8 Options</b>	<b>LED</b> One end hot LED tube	<b>SN</b> Satin Nickel	<b>30</b> 3000K
		<b>25</b> 36 inch T8	<b>2 ft.</b>			<b>35</b> 3500K
	<b>2</b> 2 Lamps	<b>32</b> 48 inch T8	<b>L7W</b> 7 Watts 950 Lumens	<b>Keystone</b>	<b>40</b> 4000K	
		<b>54<sup>1</sup></b> 46 inch T5HO	<b>L9W</b> 9 Watts 1050 Lumens	<b>3 ft.</b>	<b>50</b> 5000K	
			<b>L12W</b> 12 Watts 1250 Lumens	<b>Keystone</b>		
			<b>L12W</b> 12.5 Watts 1750 Lumens	<b>4 ft.</b>		
			<b>LEDL15W</b> 15 Watts 1740 Lumens	<b>Keystone</b>		
			<b>LEDL18W<sup>2</sup></b> 18 Watts 2500 Lumens	<b>T5 Options</b>		
			<b>LEDL25W</b> 25 Watts 3300 Lumens			

8. LAMP BRAND	9. INVERTER(O) <sup>4</sup>
<b>Blank</b> House Brand Lamp (Savegreen)	<b>INV5</b> 5W Integrated Inverter
<b>KEY</b> Keystone Brand	
<b>JAM<sup>3</sup></b> James Brand	

**NOTES:**

- <sup>1</sup>Only Available in 840 & 850
  - <sup>2</sup>Premium Lamp Option
  - <sup>3</sup>Special Order
  - <sup>4</sup>O is optional
- Dimensions and specifications subject to change without notice.



Note: In order for UL safety certification to be valid, only approved lamps may be installed in the fixture and must be shipped with the fixture from the factory.