



**JOB NAME:**

**CAT#:**

**TYPE:**



The most economical, practical, and user friendly series of LED fixtures with energy savings, quality of light, long life and hassle-free maintenance/ EZLED fixtures are UL listed with the latest LED T8 bypass lamps. These fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required). They also provide the flexibility to change the wattage and color temperature at any time. Are you concerned about maintenance with an LED array and driver fixture? EZLED resolves that issue by utilizing a self-contained LED lamp that fits into your fixture just like the classic fluorescent tube. The fixture performance will evolve over time with the evolution of the T8 LED lamp technology, and our five-year warranty guarantees a reliable, high quality product.

Specification grade, surface mounted direct/indirect center diffuser luminaire provides smooth and uniform ambient lighting for all commercial and industrial buildings with recessed configurations. Reflected light from matte surfaces providing a softened perforated appearance to the modern office environment.

- Direct/Indirect mimics perforated appearance providing low glare
- Matte white reflective surfaces for soft, uniform light distribution
- Recessed perforated center diffuser with acrylic overlay
- UL listed for damp location

**CONSTRUCTION**

Housing is die-formed and embossed code gauge steel. Luminaire body finish is high reflectance baked white enamel, with matte white reflectors. Wiring knockouts are provided on the back of housing. Center diffuser snaps into place; no tools are required for removal. Diffuser is perforated to maintain even brightness and provided with an internal, acrylic overlay to obscure lamps.

**Lamp Specifications**

Our EZLED fixtures come standard with SaveGreen T8 LED lamps. They are available in 2 or 4 foot sizes in different wattage, lumens, and color temperature options (see lamp options and specifications at [www.savegreenlighting.com](http://www.savegreenlighting.com)).

- L70 > 50000 hrs.
- Operating temperature: -20°C to 50°C
- Color Temperature: 3500K, 4000K, 5000K
- G13 pins (same as fluorescent linear T8 bipin)
- AC100-277V
- Integral driver (non-isolated) eliminates the need for external driver or ballast
- Environmentally friendly, no mercury used
- UL Classified
- Min CRI 80
- 5 year warranty

**Optional Dimming**

The 4 foot lamps are available with a dimming option. Specially designed dimming lamps require an external driver that runs 1 or 2 lamps (more than 2 lamps require multiple external drivers).

**Emergency Options**

The standard EZLED lamps require an inverter or an all-in-one emergency kit that includes LED array, battery, and driver. Dimmable T8 LED with external driver works with standard LED EM in it.



**Note: In order for UL safety certification to be valid, only approved lamps may be installed in the fixture and must be shipped with the fixture from the factory.**



**JOB NAME:**

**CAT#:**

**TYPE:**

**ORDERING**

EXAMPLE: SRDIS 22 3 32 LEDL18W PF 35 INV5

**SRDIS**

1. SERIES	2. SIZE	3. # OF LAMPS	4. LAMP TYPE	5. LAMP WATTAGE	6. LENS	7. COLOR TEMP
SRDIS	14 1x4	1 1 Lamp	17 24" T8	<u>T8 Options</u>	PF Perforated Basket	30 3000K
	22 2x2	2 2 Lamps	32 48" T8	<u>2ft.</u>	FR Frosted	35 3500K
	24 2x4	3 3 Lamps	54 46" T5HO	LEDL7W 7 Watts 950 Lumens	RL Ribbed Acrylic	40 4000K
				LEDL9W 9 Watts 1050 Lumens		50 5000K
				<u>4ft.</u>		
				LEDL12W 12.5 Watts 1750 Lumens		
				LEDL15W 15 Watts 1740 Lumens		
				LEDL18W 18 Watts 2500 Lumens		
				<u>T5 Options</u>		
				LEDL25W 25 Watts 3300 Lumens		

8. LAMP BRAND	9. WHIP	10. INVERTER
Blank House Brand (Savegreen)	WP 6' whip, 3 wire	INV5 5W Integrated Inverter
KEY Keystone		
JAM James Brand (Special Order)		

Dimensions and specifications subject to change without notice.



Note: In order for UL safety certification to be valid, only approved lamps may be installed in the fixture and must be shipped with the fixture from the factory.