



Texas Fluorescents  
Reinvented



# WPU SERIES

## Wall Puff Linear Fixture



**SG**  
Inside



Contemporary narrow white cloud 1 or 2 light vanity has rounded corners and can be mounted vertically or horizontally. Diffuser fully encloses the fixture providing a clean appearance. The X1LED WPU series utilize efficient LED T8 lamps that provide high lumen output with efficient energy savings. Since they don't require any ballast or driver the only component that will ever need changing is the LED T8 lamp. The lamps are warranted for five years. Unlike WPU series that utilize LED arrays and drivers these fixtures have the flexibility to change wattage, lumens, and color temperature simply by changing the lamps without the need to call a licensed electrician.

### LAMP

1 or 2 lamp positions

### CONSTRUCTION

The wiring channel is formed from 22-gauge steel and is provided with standard mounting holes and wiring access. Housing is finished in lighting grade baked gloss white enamel paint.

### ELECTRICAL

This unit can be ordered in the following options: with UL listed instant-start, electronic high power factor ballast; 120-277 Universal 50/60Hz AC (MV suffi x) S designates normal power factor, 120V, residential grade ballast. Consult for other ballast options.

### MOUNTING

Diffuser is vacuum-formed .125" thick crepe matte texture. Diffuser is secured with a screw on each end.

### SIZE W x L x H in inches

WPU217 - 6.0"W x 27.0L" x 2.75H"

WPU232 - 6.0"W x 51.0L" x 2.75H"

### X1 LED

The most economical, practical and user friendly series of LED fixtures with the energy savings, quality of light, long life and hassle-free maintenance. X1 LED fixtures are UL Listed with the latest LED T8 Bypass lamps. Fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required) and have flexibility to change wattage and color temperature any time. Fixture performance will evolve over time with the evolution of the T8 LED lamp technology. Concerned about maintenance with an LED array and driver fixture, X1 LED solves that by utilizing a self contained LED lamp that fits into fixture just like a fluorescent lamp.

### Lamp Specifications:

Our T8 LED lamps are available in 2 or 4 ft sizes in different wattage, lumens and color temperature options. Savegreen Lighting is a premier supplier of LED T8 lamps and makes a variety of Bypass T8 lamps to meet the needs of your special application. Options include more energy efficient 12W, 15W and 17W lamps with Premium 10 Year warranty as well as high output options up to 3500 lumens. Double ended LED T8 lamps are also available. See lamp options and specs at [www.savegreenlighting.com](http://www.savegreenlighting.com).

### Optional Dimming Options:

The 4 FT lamps are available with two dimming options; Specially designed dimming lamps require an external driver that runs 1 or 2 lamps. So more than 2 lamps require multiple external drivers or Consult for Bypass Type B lamps that can be dimmed without any external driver and dim with standard 2 wire dimming. See dimming options and specs at [www.saylite.com](http://www.saylite.com).

### Emergency Options:

The standard X1 LED Lamps require an inverter or an All-in-one emergency kit that includes LED array, battery and driver. Dimmable T8 LED with external driver works with standard LED EM. For a 5 watt inverter that is similar to adding a 500 Lumen emergency in a conventional fluorescent fixture, add "INV5W" to the end of the item number. This will allow 5 watts of one lamp to work in emergency mode. Or add "EMKT12" to the end of the item number to get a 12W stand alone emergency kit in the fixture that comes with a driver, battery and small LED array that works in Emergency mode. See emergency options and specs at [www.saylite.com](http://www.saylite.com).



Note: In order for UL safety certification to be valid, only approved lamps may be installed in the fixture and must be shipped with the fixture from the factory.

### Saylite, Texas Fluorescents Reinvented

2055 Luna Rd. Suite 142 Carrollton, TX 75006

Phone: 972-247-3171 Fax: 972-247-0200

[www.saylite.com](http://www.saylite.com) email: [sales@saylite.com](mailto:sales@saylite.com)

|                 |
|-----------------|
| Catalog Number: |
| Notes:          |



Texas Fluorescents  
Reinvented



**Ordering Options**

(Fixtures below include LED T8 Lamp LT8ABP48L18W2250LXXK. For Other Lamp Options See below and Replace LNXXX with short code below. Specify without Lamps by removing LNXXX)

| ITEM NO.        | DESCRIPTION  |
|-----------------|--|
| WPU217X1LN15W40 | 2ft. Wall 3750 Lumen 2x15W LED T8 4000K Lamps Included |
| WPU232X1LN18W40 | 4ft. Wall 4500 Lumen 2x18W LED T8 4000K Lamps Included |

Change 40 to 35 or 50 for different Kelvin. Change Lamp Wattage to 13W on 2FT or 15W on 4FT

For 5W Emergency, Add INV5 at the End of Item Number for KTEMRGLED5500AC. See other options at [www.saylite.com](http://www.saylite.com)  
 For fixtures wired for double ended lamps, change X1 to X2 and see the Savegreen Lamps below for the proper Double Ended Lamp. For fixtures without lamps included, remove the "LNXXX" at the end of the item number and have X1 or X2 for Single or Double Ended wiring.

|   |
|---|
| <p><b>LN18W40 - Lamp Specification</b><br/>         50,000 Hour Life with 5 Year Warranty<br/>         Beam Angle 140 Degree<br/>         Aluminum Base and Aluminum Housing with Glass Cover<br/>         Operating Temperature: - 20C to 50C<br/>         Color Temperature: 3500K, 4000K, 5000K<br/>         G13 Pins (Same as Fluorescent Linear T8 Bipin)<br/>         AC100 – 277V without Ballast<br/>         Single Ended or Double Ended Power (If not specified use X1 Single Ended Power)</p> |
|---|

**Savegreen T8 or T5 LED Lamp Options**

To include one of these lamps in fixture, remove "LNXXX" and add Savegreen Inside code below.  
 (See [www.savegreenlighting.com](http://www.savegreenlighting.com) for specification sheets or more information on these lamp options.)

| VERSION      | SAVEGREEN INSIDE | SAVEGREEN ITEM NO.     |
|--------------|------------------|------------------------|
| Popular      | SGB15W35         | LT8BG48L15W1740LXXK    |
| Standard     | SGS29W35         | LT8BGC24L9W1050LXXK    |
| Standard     | SGS312W35        | LT8BGC36L12W1200LXXK   |
| Standard     | SGS15W35         | LT8BGC48L15W1740LXXK   |
| Premium      | SGP12W35         | L10T8BGC48L12W1750LXXK |
| Premium      | SGP15W35         | L10T8BGC48L15W2000LXXK |
| Premium      | SGP18W35         | L10T8BGC48L18W2500LXXK |
| High Output  | SGH26W40         | LT8BGC48L26W3500LXXK   |
| Double Ended | SGD18W35         | LT8BDGC48L18W2100LXXK  |
| T5HO         | SGT525W40*       | LT5BG46L25W3300LXXK    |
| Magic        | SGM18W35K        | LT8ABP48L18W2250LXXK   |
| Magic        | SGM18W35K        | LT8ABP48L15W1875LXXK   |
| Magic        | SGM215W35K       | LT8ABP24L15W1875LXXK   |

10-YEAR  
WARRANTY

Change 35 to 40 or 50 for different Kelvin.  
 \*For T5, CCT 40K and 50K available.



Note: In order for UL safety certification to be valid, only approved lamps may be installed in the fixture and must be shipped with the fixture from the factory.

Saylite, Texas Fluorescents Reinvented  
 2055 Luna Rd. Suite 142 Carrollton, TX 75006  
 Phone: 972-247-3171 Fax: 972-247-0200  
[www.saylite.com](http://www.saylite.com) email: [sales@saylite.com](mailto:sales@saylite.com)

|                 |
|-----------------|
| Catalog Number: |
| Notes:          |